

## OUR HIGH GRASS MOWERS ARE CALLED ALLMÄHER®

If a high grass mower makes headway on rough terrain, steep slopes, in high grass and undergrowth while easily manoeuvring around obstructions and trees, chops the cuttings and can withstand harsh conditions, then we call it Allmäher®.

Invented on the steep slopes of southern German vineyards and constantly refined by 60 years of experience. Made for densely overgrown areas, embankments, roadsides with high grass, weeds and undergrowth. Ideal for properties where areas between trees and shrubbery is mown only a few times a year. Whether in the forest, on private property or public areas. Over the years the application areas have multiplied, because the Allmäher® is continuously getting further developed by the engineers at AS-Motor.

Allmäher® (all-mower), the name says it all: There is hardly a challenge that an Allmäher® cannot handle.



## FOR PRIVATE USERS AND PROS: ALLMÄHER® FROM AS-MOTOR

### MOWERS FOR STEEP SLOPES

The models like AS 28 2T ES, AS 63 2T ES and AS 65 2T ES with their 2-stroke engines offer the highest level of all-terrain mobility in their class. However, the AS 65 4T B&S and the AS 73 4T B&S with their especially adapted 4-stroke engines are also fully capable of working on slopes at high work rates.

### THE ROBUST CLASSICS


Since 1959 models like the AS 21 and AS 26 have been earning the reputation of the utmost reliability. Whether on the meadow behind the house, on the meadow orchard or caring for the weekend property, these Allmähers do the job.

### AS 63 ALLMÄHER® – THE ALL-ROUNDER

The AS 63 Allmäher® is the entry level machine in the semi-professional class. With product advantages, such as limited-slip differential, variable speed, automatic parking brake, blade clutch, vibration damping and AS cross-blade system, it is a true all-rounder. There are three engine variants to choose from for your application area: The AS 2-stroke engine for steep slopes and maximum cutting force, the robust B&S 4-stroke engine for slight inclines or the quiet Honda 4-stroke engine for moderate terrain.

[www.as-motor.com](http://www.as-motor.com) Application videos on  YouTube

Your service dealer



AS-Motor Germany  
GmbH & Co. KG  
Ellwanger Straße 15  
D-74424 Bühlertann  
Germany

info@as-motor.de  
www.as-motor.com

**AS**  
MOTOR



**HIGH GRASS, STEEP  
AND DIFFICULT TERRAIN,  
ALLMÄHER® FOR EACH  
OPERATION AREA.**

ALL TERRAIN MOWERS  
MADE IN GERMANY

**AS**  
MOTOR

# AS-MOTOR ALLMÄHER®

## AS 21 4T B&S



B&S 4-stroke engine, 190 ccm  
Rated power 3.6 kW (4.9 hp),  
max. 4.1 kW (5.5 hp).  
Cutting height 55 - 80 mm,  
cutting width 51 cm.

## AS 21 4T Comfort



B&S 4-stroke engine, 190 ccm  
Rated power 3.6 kW (4.9 hp),  
max. 4.1 kW (5.5 hp).  
Cutting height 55 - 80 mm,  
cutting width 51 cm.

## AS 21 2T ES

EASY START



AS 2-stroke engine, 165 ccm, EasyStart.  
Rated power 4.0 kW (5.4 hp),  
max. 4.4 kW (6.0 hp).  
Cutting height 55 - 80 mm,  
cutting width 51 cm.

## AS 26 2T ES

EASY START



AS 2-stroke engine, 165 ccm, EasyStart.  
Rated power 4.0 kW (5.4 hp),  
max. 4.4 kW (6.0 hp).  
Cutting height 55 - 80 mm,  
cutting width 63 cm.

EASY START



## AS 28 2T ES

AS 2-stroke engine, 165 ccm, EasyStart.  
Rated power 4.0 kW (5.4 hp),  
max. 4.4 kW (6.0 hp).  
2-speed transmission, brake,  
inflatable tyres.  
Cutting height 55 - 130 mm,  
cutting width 63 cm.

## AS 62 4T B&S



B&S 4-stroke engine, 190 ccm.  
Rated power 3.7 kW (5.1 hp),  
max. 4.1 kW (5.5 hp).  
Blade clutch, Variomatic,  
AS cross-blade, freewheeling  
drive, VibrationProtect.  
Easy to transport (folds together).  
Cutting height 50 - 100 mm,  
cutting width 61 cm.

## AS 63 2T ES

EASY START



AS 2-stroke engine, 165 ccm, EasyStart.  
Rated power 4.0 kW (5.4 hp),  
max. 4.4 kW (6.0 hp).  
Blade clutch, Variomatic AS cross-blade,  
limited slip differential, automatic  
parking brake, VibrationProtect.  
Easy to transport (folds together).  
Cutting height 50 - 100 mm,  
cutting width 61 cm.

## AS 63 4T B&S



B&S 4-stroke engine, 190 ccm.  
Rated power 4.1 kW (5.5 hp),  
max. 4.1 kW (5.5 hp).  
Blade clutch, Variomatic, AS cross-  
blade, limited slip differential, automat-  
ic parking brake, VibrationProtect.  
Easy to transport (folds together).  
Cutting height 50 - 100 mm,  
cutting width 61 cm.

## AS 63 4T Honda



Honda 4-stroke engine, 163 ccm.  
Rated power 3.2 kW (4.3 hp),  
max. 3.2 kW (4.3 hp).  
Blade clutch, Variomatic, AS cross-blade,  
limited slip differential, automatic  
parking brake, VibrationProtect  
Easy to transport (folds together)  
Cutting height 50 - 100 mm,  
cutting width 61 cm.

## AS 65 2T ES

EASY START



AS 2-stroke engine, 165 ccm, EasyStart.  
Rated power 4.0 kW (5.4 hp), max. 4.4 kW (6.0 hp).  
5-speed, switchable limited slip differential,  
automatic parking brake, AS cross-blade,  
variable cutting height adjustment.  
Cutting height 50 - 100 mm,  
cutting width 65 cm.

## AS 65 4T B&S

B&S 4-stroke engine with oil pump, 344 ccm.  
Rated power 7.6 kW (10.3 hp), max. 9.7 kW (13.0 hp).  
5-speed, switchable limited slip differential,  
automatic parking brake, AS cross-blade,  
variable cutting height adjustment.  
Cutting height 50 - 100 mm,  
cutting width 65 cm.



## AS 73 4T B&S

B&S 4-stroke engine with oil pump, 344 ccm.  
Rated power 7.6 kW (10.3 hp), max. 9.7 kW (13.0 hp).  
5-speed, switchable limited slip differential,  
automatic parking brake, AS cross-blade,  
switchable blade speed, variable cutting  
height adjustment.  
Cutting height 50 - 100 mm,  
cutting width 73 cm.

